PRODUCT DATASHEET

TECHNICAL DOCUMENTATION

HUMAN-PRESENCE RADAR MODULE

PS-24C-03

Ceiling Presence Sensor — 24 GHz, BLE

Document No.	PS-TDS-24C-03	**Version**	V1.0
Model	PS-24C-03	**Issue Date**	2026-11-08

This document is a product datasheet template of {SITE_BRAND}. No part may be reproduced or distributed without permission.

Document Information

Document title	presencesensor.com Product Datasheet	**Model**	PS-24C-03
Series	Human Presence Detection (presence)	**Document No.**	PS-TDS-24C-03
Version	V1.0	**Issue date**	2026-11-08
Prepared by	PresenceSensor Engineering Team	**Reviewed by**	Product Department
Classification	Public		

Table A Document information

Contents

1 Product Overview

2 Key Features

3 Applications

4 Technical Specifications

5 Pin Definition

6 Dimensions and Installation

7 Communication and Configuration

8 Model Selection

9 Document Downloads

10 Ordering Information and Support

Appendix A Revision History

1 Product Overview

Ceiling-mounted 24 GHz radar sensor for human presence with Bluetooth Low Energy. It detects breathing, micro-motion and movement, switches the lighting load directly, and is configured over BLE from the app.

- Model: PS-24C-03
- Product: Ceiling Presence Sensor — 24 GHz, BLE
- Series: Human Presence Detection (presence)
- Frequency band: 24 GHz

2 Key Features

- 24 GHz radar detects breathing, micro-motion and movement
- Bluetooth Low Energy configuration from the app
- Motion and micro-motion detection Ø4–7 m (reference)
- 120° field of view; recommended ceiling height 2.7–3 m
- Switched output up to 300 W

Features are typical for this series. Refer to the latest datasheet for model-specific values.

3 Applications

Lighting control in hotel rooms, corridors and residences where a local, gateway-free setup is preferred.

4 Technical Specifications

Frequency band	24 GHz	**Modulation**	—
Supply voltage	110–260 V AC	**Operating current**	—
Average power	≤300 W	**Detection range**	—
Field of view	120°	**Range resolution**	—
Interface	Bluetooth Low Energy	**Output**	VOUT / VIN / GND / GND (P1)
Operating temp.	—	**Storage temp.**	—
Dimensions	Ceiling, Ø50 mm cut-out	**Antenna**	—

Certification	—	**Remarks**	BLE is used for setup; scene linkage requires a compatible gateway if the project needs automation.

Table 1 Technical specifications. Subject to the latest datasheet without prior notice.

5 Wiring Terminals

The module uses a 5-pin header/socket interface defined as follows:


Pin	Name	Type	Description
1	VOUT	Output	Switched output, lighting load ≤300 W
2	VIN	Power	Mains input 110–260 V
3	GND	Power	Ground
4	GND	Power	Ground
5	—	—	—

Table 2 Pin definition. Refer to the datasheet of the specific model.

6 Dimensions and Installation

6.1 Dimensions


Outline dimensions per the manufacturer drawing (unit: mm).



Product illustration

6.2 Installation

Ceiling cut-out Ø50 mm. Switch off the main breaker, wire the P1 connector, pass the unit through the cut-out and rotate the mounting tabs.



Installation

Refer to the Installation Guide of the specific model for the relationship between mounting height, tilt angle and detection coverage.

7 Communication and Configuration


7.1 Communication Protocol

The app connects over BLE to read presence state and set distance, sensitivity and delay.

7.2 Configuration Tool

Configuration is done through the platform the device is paired with.

7.3 Typical Application Circuit



Wiring terminals

8 Model Selection

The series is organized by frequency band and sensing function. Select a model based on detection range, mounting method and interface.

Model	Band	Series	Typical Application
PS-24C-03	24G	Human Presence Detection	Indoor presence detection, smart lighting, building energy saving, security automation, elderly care
PS-24C-01	24G	Human Presence Detection	Indoor presence detection, smart lighting, building energy saving, security automation, elderly care
PS-24C-02	24G	Human Presence Detection	Indoor presence detection, smart lighting, building energy saving, security automation, elderly care
PS-24C-04	24G	Human Presence Detection	Indoor presence detection, smart lighting, building energy saving, security automation, elderly care

Table 3 Model selection. See the product center on the website for the complete model list.

9 Document Downloads

The following documents are available for this model on its product page at {SITE_BRAND}.

Category	File	Version	Description
Development	—	—	Datasheet / user manual / protocol
Development	—	—	Schematics / footprint / 3D model
Application	—	—	Configuration tool
Utility	—	—	Serial driver / terminal

Table 4 Document list. File names and versions follow the download page.

10 Ordering Information and Support

Please specify the model, quantity and interface when ordering. For samples, quotations or technical support:

- Website: presencesensor.com
- Products: presencesensor.com/products
- Support: sales@presencesensor.com
- Sales: sales@presencesensor.com

Appendix A Revision History

Version	Date	Description	Prepared / Reviewed
V1.0	2026-11-08	Initial release	PresenceSensor Engineering Team
—	—	—	PresenceSensor Engineering Team
—	—	—	PresenceSensor Engineering Team

Table 5 Revision history. Update the version and date for every revision.